LED Zubehör
LED accessories

PWM-Modul extern, IP54

Artikel-Nr.:	210700-05
EAN:	4260556625409

Bestell-Nr.:	210700-05
Modell:	Dimmbox, PWM Modul
Bauform:	Aufbaugerät mit Befestigung über Langloch
Durchgangsspannung:	24V DC
Strombelastung max.:	4 A
Belegung PIN 1 Input/Output:	24V DC+ / nicht belegt
Belegung PIN 2 Input/Output:	digitaler Eingang / nicht belegt
Belegung PIN 3 Input/Output:	GND / GND
Belegung PIN 4 Input/Output:	digitaler Eingang / +24V out
Belegung PIN 5 Input/Output:	24V DC+ / nicht belegt
Eingang/Ausgang:	M12 Buchse / M12 Stecker A kodiert
Material Gehäuse:	Kunststoff, schwarz
Abmessungen (mm):	122 x 33 x 29
Schutzart:	IP54
Gewicht:	100 g
Bruttogewicht:	150 g

Steckerbelegung Steuerpins, 5poliger M12A Stecker

0 = GND oder n.c.
1 = 24V DC+

Licht-Status / Dimm-Level	PIN 2	PIN 4	PIN 5
100% Helligkeit	1	0	0
90% Helligkeit	0	0	1
75% Helligkeit	0	1	0
66% Helligkeit	0	0	0
50% Helligkeit	0	1	1
33% Helligkeit	1	0	1
25% Helligkeit	1	1	0
10% Helligkeit	1	1	1





Die Entsorgung erfolgt gemäß den länderspezifischen Vorschriften und Rücknahmeverpflichtungen für B2B Produkte zum Recyceln von Elektro- und Elektronikgeräten. (WEEE-Richtlinie)

Irrtümer, Systemfehler und Änderungen vorbehalten. /
Errors and technical changes excepted. 05.2022

LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com | Shop.led2work.com

PWM-module external, IP54

Item number:	210700-05
EAN:	4260556625409

Order number:	210700-05
Model:	dim box, PWM module
Type:	mounted device with mounting via elongated hole
Nominal output voltage:	24V DC
Output amperage max.:	4 A
PIN 1 allocation input/output	24V DC+ / not used
PIN 2 allocation input/output	digital input / not used
PIN 3 allocation input/output	GND / GND
PIN 4 allocation input/output	digital input / +24V out
PIN 5 allocation input/output	24V DC+ / not used
Input/output	M12 socket / M12 plug A-type encoded
Material housing	plastics, black
Dimensions (mm):	122 x 33 x 29
Degree of protection:	IP54
Weight (net):	100 g
Gross weight:	150 g

Allocation control pins, M12A plug, 5-pin

0 = GND or n.c.
1 = 24V DC+

light status / dim level	PIN 2	PIN 4	PIN 5
intensity 100%	1	0	0
intensity 90%	0	0	1
intensity 75%	0	1	0
intensity 66%	0	0	0
intensity 50%	0	1	1
intensity 33%	1	0	1
intensity 25%	1	1	0
intensity 10%	1	1	1





Disposal is carried out in accordance with the country-specific regulations and take-back obligations for B2B products for the recycling of electrical and electronic equipment. (WEEE Directive)

2021_06_LED2WORK_Datenblatt Netzteil doppelseitig_3.0_2022_02.08

LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com | Shop.led2work.com