LED2WORK
INTELLIGENCE IN LIGHT

LED Maschinenleuchte
LED machine luminaire

TUBELED_70, 60°, 1100 mm, 24V DC

Artikel-Nr.:	110514-02
EAN:	4260556621364
Zolltarifnr.:	94054099

Bestellnr.:	110514-02
Modell:	TUBELED_70 DC
Bauform:	LED Aufbauleuchte für Maschinen
Leuchtmittel:	High Power LED
Lampenleistung:	~60 W
Lampenlichtstrom:	6104 lm
Lampenlichtausbeute:	ca. 116 lm/W
Lichtverteilung:	direkt
Lichtfarbe:	Tageslichtweiß (5200 - 5700K)
Anschlusswert Leuchte:	24V DC ± 10%
Anschluss Leuchte:	M12 A-kodiert
Schutzart:	IP67/IP69K
Schutzklasse:	III
Entblendung:	opalweiß
Abstrahlwinkel:	60°
Betriebstemperatur:	-30... +70 °C
Farbwiedergabe (Ra):	> 80
Lampenlebensdauer:	> 60.000 h
Material Gehäuse:	Aluminium
Material Abdeckung:	Sicherheitsglas gefrostet, sprungsicher
Höhe [B] x Breite [C]:	Ø 70 mm
Länge [A]:	1100 mm
Gewicht:	2950 g
Bruttogewicht:	3750 g
Risikogruppe:	freie Gruppe
Kennzeichnung:	CE, ETL Listed
Befestigungszubehör:	optional
Dimmbar:	optional über Zubehör
Gefertigt in:	Deutschland
Besonderheit:	Retrofitting: genormte LED Rohrleuchte zum 1:1 Austausch, 100% CNC geeignet

Intertek
5003529



110514-02



Lampenlebensdauer in Betriebstunden (L80/B10)

LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com | Shop.led2work.com

LED Maschinenleuchte
LED machine luminaire

TUBELED_70, 60°, 1100 mm, 24V DC

Item number:	110514-02
EAN:	4260556621364
Customs tariff number:	94054099

Order number:	110514-02
Model:	TUBELED_70 DC
Type:	LED surface-mounted luminaire for machines
Illuminant:	High Power LED
Power consumption:	~60 W
Lamp luminous flux:	6104 lm
Lamp luminous efficiency:	ca. 116 lm/W
Light distribution:	direct
Light colour:	daylight white (5200 - 5700K)
Connected load:	24V DC ± 10%
Connection (connector):	M12 A-type encoded
Degree of protection:	IP67/IP69K
Class of protection:	III
Glare-free	opal white
Beam angle (optics):	60°
Operating temperature:	-30... +70 °C
Colour rendering (Ra):	> 80
Lamps lifetime:	> 60,000 h
Housing material:	aluminium
Cover material:	Safety glass, frosted, shatterproof
Height [B] x Width [C]:	Ø 70 mm
Length [A]:	1100 mm
Weight (net):	2950 g
Gross weight:	3750 g
Risk group (DIN EN 62471):	free group
Marking:	CE, ETL Listed
Mounting accessories:	optional
Dimmable:	via optional accessory
Made in:	Germany
Feature:	Retrofitting: standardised LED luminaire for 1:1 replacement, 100% CNC approved

Intertek
5003529



110514-02



Lamps lifetime in operation hours (L80/B10)

LED2WORK GmbH | Stuttgarter Straße 13 A | 75179 Pforzheim | Germany
T: +49 7231 44920-00 | info@led2work.com | www.led2work.com | Shop.led2work.com